

County Surveyor's Record, Douglas County, Oregon

17471 Dependent Resurvey of a Portion of the West Boundary,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS							
37.25	Ravine, drains S. 80° E.; asc. over S. slope.						
37.66	The closing cor. of secs. 24 and 25, T. 19 S., R. 9 W., hereinafter described. Ascend over S. slope.						
38.45	Spur, slopes S. 55° E.; desc. over NE. slope.						
39.88	The 1/4 sec. cor. of sec. 19 only, hereinbefore described.						
	From the cor. of secs. 18 and 19 only, hereinbefore described. N. 0° 55' W., on the W. bdy. of sec. 18. Descend over NW. slope, through heavy timber and dense undergrowth.						
0.12	An original line tree, a fir, 76 ins. diam., with 2 notches each on N. and S. sides. N. 0° 55' W., beginning new measurement.						
2.80	Creek, 7 lks. wide, course S. 20° W.; asc. over broken E. slope.						
12.50	Spur, slopes E.; desc. over NE. slope.						
15.40	Creek, 2 lks. wide, course S. 80° E.; asc. over SE. slope.						
18.28	The N 1/16 sec. cor. of sec. 24 only, T. 19 S., R. 9 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td style="border-right: 1px solid black; padding-right: 5px;">N 1/16</td><td style="padding-left: 5px;"> </td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 24</td><td style="padding-left: 5px;"> </td></tr> <tr><td colspan="2" style="text-align: center;">1957</td></tr> </table> </div> from which the remains of bearing trees mkd. by Tillman, Holm, and Brooks A root hole, bears S. 34 1/2° W., 78 lks. dist., alongside of which is a down, decayed fir, 19 ins. diam., no marks visible. A fir, 21 ins. diam., bears N. 83 3/4° W., 39 lks. dist., with healed blaze. and a new bearing tree A fir, 70 ins. diam., bears S. 14 1/2° W., 73 1/2 lks. dist., mkd. N 1/16 S24 BT. Ascend over broken SE. slope.	N 1/16		S 24		1957	
N 1/16							
S 24							
1957							
20.43	The S 1/16 sec. cor. of sec. 18 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 1/16</td><td style="padding-left: 5px;"> </td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 18</td><td style="padding-left: 5px;"> </td></tr> <tr><td colspan="2" style="text-align: center;">1957</td></tr> </table> </div> from which bearing trees mkd. by Tillman, Holm, and Brooks	S 1/16		S 18		1957	
S 1/16							
S 18							
1957							