

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the West Boundary 17472
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS									
	<p>A maple, 23 ins. diam., bears N. 32 1/2° E., 67 lks. dist., with scribe marks S 1/16 S18 BT visible on open blaze.</p> <p>A fir, 25 ins. diam., bears S. 24 1/2° E., 101 lks. dist., with healed blaze.</p> <p>Ascend along broken E. slope.</p>								
22.90	Spur, slopes S. 70° E.; desc. over broken NE. slope.								
29.20	Ravine, drains N. 70° E.; asc. over SE. slope.								
38.00	Spur, slopes S. 80° E.; desc. over NE. slope.								
38.48	<p>The closing cor. of secs. 13 and 24, T. 19 S., R. 9 W., hereinafter described.</p> <p>Descend over NE. slope.</p>								
40.00	Creek, 1 lk. wide, course S. 70° E.; asc. over SE. slope.								
40.99	<p>The 1/4 sec. cor. of sec. 18 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td style="border-right: 1px solid black; padding: 0 5px;">T 19 S</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">1/4 S 18</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 8 W</td></tr> <tr><td style="padding: 0 5px;">1957</td></tr> </table> </div> <p>from which bearing trees mkd. by Tillamn, Holm, and Brooks</p> <p>A fir, 50 ins. diam., bears N. 77 1/2° E., 41 lks. dist., with healed blaze.</p> <p>A fir, 33 ins. diam., bears S. 66° E., 19 lks. dist., with healed blaze.</p> <p>Land, mountainous. Soil, clay loam. Timber, fir, cedar, hemlock, alder, maple, and yew; undergrowth, vine maple, salmonberry, ocean spray, huckleberry, salal, and fern.</p>	T 19 S	1/4 S 18	R 8 W	1957				
T 19 S									
1/4 S 18									
R 8 W									
1957									
<p>Corrective Dependent Resurvey of a Portion of the Subdivisional Lines, T. 19 S., R. 9 W., Willamette Meridian, Oregon</p>									
<p>(Restoring the survey by Henry L. Chandler in 1899, correcting the resurvey by Thomas A. Tillman, Robert L. Holm, and Floyd A. Brooks in 1957-58, and correcting the resurvey by Donald R. Beck and Peter a Peterson in 1968-76)</p>									
<p>From the cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td style="padding: 0 5px;">T 19 S</td><td style="padding: 0 5px;">R 9 W</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 23</td><td style="padding: 0 5px;">S 24</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 26</td><td style="padding: 0 5px;">S 25</td></tr> <tr><td colspan="2" style="padding: 0 5px;">1968</td></tr> </table> </div>		T 19 S	R 9 W	S 23	S 24	S 26	S 25	1968	
T 19 S	R 9 W								
S 23	S 24								
S 26	S 25								
1968									