

# County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 19 S., R. 9 W.,  
Willamette Meridian, Oregon

17474

CHAINS																			
	<p style="text-align: center;">A maple, 23 ins. diam., bears S. 43° W., 34 lks. dist., mkd. 1/4 S25 BT.</p> <p>Ascend over broken SW. slope.</p>																		
41.03	<p>Leave timber, edge bears N. and S., thence across recent- ly logged area.</p>																		
60.855	<p>Point for the E 1/16 sec. cor. of secs. 24 and 25.</p> <p>From this point, the E 1/16 sec. cor. of secs. 24 and 25, erroneously positioned by Beck and Peterson, bears N. 16° 35' W., 0.098 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the official record.</p> <p>I remove the iron post, and at the true corner point</p> <p>Reset the iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr> <td style="padding: 0 10px;">E 1/16</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 24</td> <td style="padding: 0 10px;"></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">S 25</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">1983</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">1968</td> <td></td> </tr> </table> </div> <p>from which the bearing trees mkd. by Beck and Peterson</p> <p style="margin-left: 40px;">A fir, 26 ins. diam., bears N. 7° E., 56 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 32 ins. diam., bears S. 41° E., 68 lks. dist., with healed blaze.</p> <p>Ascend over broken SW. slope.</p>	E 1/16	S 24			S 25			1983			1968							
E 1/16	S 24																		
	S 25																		
	1983																		
	1968																		
61.30	<p>Leave logged area, edge bears N. and S., enter heavy timber.</p>																		
71.25	<p>Spur ridge, bears N. 60° W. and S. 60° E.; asc. along broken N. slope.</p>																		
80.75	<p>Spur, slopes N. 10° E.; desc. over NE. slope.</p>																		
83.55	<p>Ravine, drains N. 15° E.; asc. over NW. slope.</p>																		
93.40	<p>Spur, slopes N. 15° E.; desc. over NE. slope.</p>																		
101.52	<p>Intersect the W. bdy. of sec. 19, T. 19 S., R. 8 W.</p> <p>The closing cor. of secs. 24 and 25, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr> <td style="padding: 0 10px;">T 19 S</td> <td style="border-left: 1px solid black; padding: 0 5px;">T 19 S</td> <td style="padding: 0 10px;"></td> </tr> <tr> <td style="padding: 0 10px;">CC</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 24</td> <td style="padding: 0 10px;">R 8 W</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">S 25</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">S 19</td> <td></td> </tr> <tr> <td style="padding: 0 10px;">R 9 W</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">1957</td> <td></td> </tr> </table> </div> <p>from which the remains of a bearing tree mkd. by Tillman, Holm, and Brooks</p> <p style="margin-left: 40px;">A decayed alder snag, 10 ins. diam., bears N. 70° W., 57 lks. dist., no marks remaining. (Record, N. 76 1/2° W.)</p>	T 19 S	T 19 S		CC	S 24	R 8 W		S 25			S 19		R 9 W				1957	
T 19 S	T 19 S																		
CC	S 24	R 8 W																	
	S 25																		
	S 19																		
R 9 W																			
	1957																		