

County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey of a Portion of the
Subdivisional Lines, T. 19 S., R. 9 W.,
Willamette Meridian, Oregon

17475

CHAINS

and bearing trees mkd. by Beck and Peterson

An alder, 19 ins. diam., bears S. 33° W., 53 lks. dist., with scribe marks T19S R9W S25 CC BT visible on the bark.

A twin maple, 35 ins. diam., bears N. 87 1/4° W., 105 lks. dist., with illegible scribe marks visible on partially healed blaze.

From this point, the 1/4 sec. cor. of sec. 19 only, T. 19 S., R. 8 W., bears N. 0° 24' W., 2.22 chs. dist., hereinbefore described.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, alder, maple, chinquapin, and yew; undergrowth, vine maple, huckleberry, ocean spray, rhododendron, salal, salmonberry, and fern.

From the 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 19 S R 9 W
1/4 $\frac{S 13}{S 24}$
1958

from which bearing trees mkd. by Tillman, Holm, and Brooks

A fir, 13 ins. diam., bears N. 77° E., 33 lks. dist., with healed blaze.

A fir, 38 ins. diam., bears S. 54 1/2° W., 31 lks. dist., with healed blaze.

The corner is located at bottom of descent, slopes S.

S. 88° 34' E., bet. secs. 13 and 24.

Ascend over SW. slope, through moderate timber and undergrowth.

3.80

Spur, slopes SE.; desc. over broken NE. slope.

20.01

Point for the E 1/16 sec. cor. of secs. 13 and 24.

From this point, the E 1/16 sec. cor. of secs. 13 and 24, erroneously positioned by Tillman, Holm, and Brooks, bears S. 10° 12' E., 0.446 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. and witnessed as described in the official record.

I remove the iron post, destroy the marks on the SW. bearing tree, and at the true corner point

Reset the iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 19 S R 9 W
E 1/16 $\frac{S 13}{S 24}$
1983
1958