

County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey of a Portion of the
Subdivisional Lines, T. 19 S., R. 9 W.,
Willamette Meridian, Oregon

17476

CHAINS

from which a bearing tree mkd. by Tillman, Holm, and Brooks

A fir, 27 ins. diam., bears N. 4 1/2° W., 66 1/2 lks. dist., with healed blaze.

and a new bearing tree

A fir, 33 ins. diam., bears S. 66 3/4° W., 33 1/2 lks. dist., mkd. E 1/16 S24 BT.

Descend over NE. slope.

22.15 Creek, 2 lks. wide, course S. 65° E.; asc. over SW. slope.

24.75 Top of ascent, slopes SE.; desc. over E. slope.

31.85 West Fork of Smith River, 15 lks. wide, course S. 10° E.; asc. over SW. slope.

33.45 Spur, slopes S. 10° W.; desc. over E. slope.

34.55 Creek, 2 lks. wide, course S. 30° W.; asc. over broken SW. slope.

52.90 Spur, slopes S. 15° W.; desc. over E. slope.

60.23 Intersect the W. bdy. of sec. 18, T. 19 S., R. 8 W.

The closing cor. of secs. 13 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

| | |
|---------|--------|
| T 19 S | T 19 S |
| CC S 13 | S 18 |
| S 24 | |
| R 9 W | R 8 W |
| 1957 | |

from which the remains of bearing trees mkd. by Tillman, Holm, and Brooks

A root hole, bears S. 78 3/4° W., 31 lks. dist., alongside of which is a down fir, 30 ins. diam., with illegible scribe marks visible on partially healed blaze.

A root hole, bears N. 28 1/2° W., 48 lks. dist.

and new bearing trees

An alder, 6 ins. diam., bears S. 78° W., 32 lks. dist., mkd. T19S R9W S24 CC BT.

An alder, 4 ins. diam., bears N. 29 1/2° W., 43 lks. dist., mkd. T19S R9W S24 CC BT.

From this point, the 1/4 sec. cor. of sec. 18 only, T. 19 S., R. 8 W., bears N. 0° 55' W., 2.51 chs. dist., hereinbefore described.

Land, mountainous.

Soil, clay loam.

Timber, fir, hemlock, cedar, alder, maple, chinquapin, and dogwood; undergrowth, vine maple, rhododendron, huckleberry, salmonberry, ocean spray, Oregon grape, salal, and fern.