

County Surveyor's Record, Douglas County, Oregon

17477

Dependent Resurvey of a Portion of the
Subdivisional Lines, T. 19 S., R. 9 W.,
Willamette Meridian, Oregon

CHAINS									
	<p>(Restoring the survey by Henry L. Chandler in 1899, the resurvey by Thomas A. Tillman, Robert L. Holm, and Floyd A. Brooks in 1957-58, and the resurvey by Donald R. Beck and Peter A. Peterson in 1968-76)</p> <hr style="width: 30%; margin: auto;"/>								
	From the cor. of secs. 23, 24, 25, and 26.								
	N. 0° 08' E., bet. secs. 23 and 24, marking and blazing the true line.								
	Descend over NE. slope, through heavy timber and dense undergrowth.								
2.00	Ravine, drains N. 60° E.; asc. over SE. slope.								
5.25	Spur, slopes NE.; desc. over N. slope.								
11.50	Creek, 1 lk. wide, course S. 70° E.; asc. over broken E. slope.								
35.30	Ravine, drains S. 20° E.; asc. over SW. slope, changing to SE. slope.								
39.05	Gravelled road, 20 lks. wide, bears N. 75° W. and S. 75° E.								
40.83	The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 19 S</td> <td style="padding: 0 10px;">T 19 S</td> </tr> <tr> <td></td> <td style="text-align: center;">1/4</td> </tr> <tr> <td style="padding: 0 10px;">S 23</td> <td style="padding: 0 10px;">S 24</td> </tr> <tr> <td></td> <td style="text-align: center;">1968</td> </tr> </table>	T 19 S	T 19 S		1/4	S 23	S 24		1968
T 19 S	T 19 S								
	1/4								
S 23	S 24								
	1968								
	from which bearing trees mkd. by Beck and Peterson								
	<p>A fir, 16 ins. diam., bears N. 35 1/4° E., 57 lks. dist., with healed blaze. (Record, hemlock, N. 31 1/2° E.)</p> <p>A fir, 14 ins. diam., bears N. 13 1/2° W., 43 lks. dist., with healed blaze. (Record, hemlock, N. 16° W.)</p>								
	<hr style="width: 20%; margin: auto;"/>								
	N. 0° 17' E., beginning new measurement.								
	Ascend over SE. slope.								
0.65	Spur ridge, bears N. 65° W. and S. 65° E.; desc. over N. slope.								
6.45	Creek, 3 lks. wide, course S. 80° E.; asc. over broken SE. slope.								
40.73	The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.								
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 19 S</td> <td style="padding: 0 10px;">R 9 W</td> </tr> <tr> <td style="padding: 0 10px;">S 14</td> <td style="padding: 0 10px;">S 13</td> </tr> <tr> <td style="padding: 0 10px;">S 23</td> <td style="padding: 0 10px;">S 24</td> </tr> <tr> <td></td> <td style="text-align: center;">1958</td> </tr> </table>	T 19 S	R 9 W	S 14	S 13	S 23	S 24		1958
T 19 S	R 9 W								
S 14	S 13								
S 23	S 24								
	1958								
	from which bearing trees mkd. by Tillman, Holm, and Brooks								