

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the
 Subdivisional Lines, T. 19 S., R. 9 W., 17478
 Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 20 ins. diam., bears N. 28 3/4° E., 55 lks. dist., with healed blaze.</p> <p>A fir, 14 ins. diam., bears S. 4 1/2° E., 27 lks. dist., with healed blaze.</p> <p>A fir, 10 ins. diam., bears S. 54° W., 39 lks. dist., with healed blaze.</p> <p>A fir, 19 ins. diam., bears N. 27 1/4° W., 35 lks. dist., with healed blaze.</p> <p>From this point, Lane County Public Works Department triangulation station "Roman 2 ECC 1973", bears S. 69° 02' W., 41.64 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. ROMAN 2 ECC 1973.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, alder, maple, and chinquapin; undergrowth, vine maple, rhododendron, salal, hazel, huckleberry, salmonberry, and fern.</p>
40.05	<p>S. 88° 34' E., bet. secs. 13 and 24.</p> <p>Descend over broken SE. slope, through heavy timber and dense undergrowth.</p> <p>The 1/4 sec. cor. of secs. 13 and 24.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, alder, maple, and chinquapin; undergrowth, vine maple, huckleberry, ocean spray, rhododendron, salal, salmonberry, and fern.</p>
	<p>Subdivision of Section 24, T. 19 S., R. 9 W., Willamette Meridian, Oregon</p>
0.40	<p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0° 11' W., on the N. and S. center line of sec. 24, marking and blazing the true line.</p> <p>Ascend over SW. slope, through heavy timber and dense undergrowth.</p>
1.05	<p>Top of ascent, slopes W.; desc. over NW. slope.</p>
8.35	<p>Ravine, drains S. 60° W.; asc. over broken S. slope.</p>
17.20	<p>Ravine, drains S. 10° W.; asc. over broken S. slope.</p>
20.32	<p>Ravine, drains S. 10° E.; asc. over broken S. slope.</p> <p>Point for the center S 1/16 sec. cor. of sec. 24.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p>C S 1/16 S 24 C 1981</p>