

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 24,
T. 19 S., R. 9 W., Willamette Meridian, Oregon

17480

CHAINS	
	From the 1/4 sec. cor. of sec. 24 only, on the E. bdy. of the Tp.
	N. 88° 50' W., on the E. and W. center lines of sec. 24.
	Descend over SW. slope.
1.65	Creek, 2 lks. wide, course S. 25° W.; asc. over SE. slope.
3.30	Spur, slopes S. 20° E.; desc. over SW. slope.
6.35	West Fork Smith River, 10 lks. wide, course S. 40° E.; asc. over NE. slope.
18.55	Spur ridge, bears N. 35° W. and S. 35° E.; desc. along broken S. slope.
36.90	Bottom of descent, slopes S. 20° E.; asc. over NE. slope.
39.70	Spur, slopes S. 15° W.; desc. 15 ft. over SW. slope.
40.565	Point for the center E 1/16 sec. cor. of sec. 24.
	Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	$C \frac{E \ 1/16}{S \ 24} C$ 1982
	from which
	A hemlock, 20 ins. diam., bears S. 51 1/2° W., 31 lks. dist., mkd. CE 1/16 S24 BT.
	A fir, 25 ins. diam., bears N. 18 1/2° W., 25 1/2 lks. dist., mkd. CE 1/16 S24 BT.
	Descend over broken SW. slope.
55.55	Creek, 5 lks. wide, course S. 60° E.; asc. over NE. slope.
60.05	Top of ascent, slopes N.; desc. 5 ft. over broken NW. slope.
60.77	The center 1/4 sec. cor. of sec. 24.
	Descend over broken NW. slope.
62.65	Ravine, drains N. 25° E.; asc. along broken N. slope.
90.90	Saddle in spur ridge, bears N. 60° W. and S. 60° E.; also, gravelled road, 25 lks. wide, bears N. 75° W. and S. 55° E. in curve; asc. over SE. slope.
93.40	Same gravelled road, 20 lks. wide, bears N. 80° E. and S. 80° W.
101.11	The 1/4 sec. cor. of secs. 23 and 24.
	From the center E 1/16 sec. cor. of sec. 24.
	N. 0° 27' W., on the N. and S. center line of the NE1/4 of sec. 24.