

County Surveyor's Record, Douglas County, Oregon

17481

Subdivision of Section 24,
T. 19 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	Ascend over broken SE. slope.
7.75	Spur ridge, bears N. 70° W. and S. 70° E.; desc. over broken N. slope.
17.35	Creek, 5 lks. wide, course S. 60° E.; asc. over S. slope.
20.25	Point for the NE 1/16 sec. cor. of sec. 24, at intersection with the E. and W. center line of the NE 1/4.
	Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	NE 1/16 S 24 1982
	from which
	A fir, 30 ins. diam., bears S. 51° E., 21 1/2 lks. dist., mkd. NE 1/16 S24 BT.
	A fir, 41 ins. diam., bears S. 55 1/2° W., 30 lks. dist., mkd. NE 1/16 S24 BT.
	Ascend over S. slope.
23.75	Spur, slopes S. 65° E.; desc. over NE. slope.
26.75	Creek, 2 lks. wide, course S. 60° E.; asc. over S. slope.
35.20	Spur, slopes S. 45° E.; desc. over broken NE. slope.
40.54	The E 1/16 sec. cor. of secs. 13 and 24.
<p>From the N 1/16 sec. cor. of sec. 24 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 88° 41' W., on the E. and W. center line of the NE 1/4 of sec. 24.</p> <p>Ascend over SE. slope, through moderate timber and dense undergrowth.</p>	
3.15	Top of ascent, slopes S.; desc. over SW. slope.
5.00	Ravine, drains S. 40° E.; asc. over broken E. slope.
10.25	Spur, slopes S. 10° W.; desc. over broken NW. slope.
17.10	Creek, 2 lks. wide, course S. 65° W.; asc. over SE. slope.
19.70	Spur, slopes S. 5° E.; desc. over SW. slope.
23.45	West Fork Smith River, 10 lks. wide, course S. 25° E.; asc. over NE. slope.
28.30	Spur, slopes S. 50° E.; desc. over SW. slope.
32.75	Creek, 1 lk. wide, course S. 35° E.; asc. over NE. slope.
36.00	Spur, slopes S. 25° E.; asc. over S. slope.
40.39	The NE 1/16 sec. cor. of sec. 24.
	Ascend over S. slope.