

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 24,
T. 19 S., R. 9 W., Willamette Meridian, Oregon

17482

CHAINS	
46.50	Top of ascent, slopes S.; desc. over SW. slope,
50.05	Creek, 2 lks. wide, course S. 60° E.; asc. over NE. slope.
52.55	Top of ascent, slopes SE.; desc. over SW. slope.
52.85	Creek, 2 lks. wide, course S. 65° E.; asc. over NE. slope.
56.40	Spur, slopes S. 70° E.; asc. over SE. slope.
60.49	The center N 1/16 sec. cor. of sec. 24.
From the E 1/16 sec. cor. of secs. 24 and 25.	
N. 0° 16' W., on the N. and S. center line of the SE 1/4 of sec. 24.	
Ascend over SW. slope, through recently logged area.	
0.10	Leave logged area, edge bears E. and W., enter heavy timber.
6.15	Spur ridge, bears N. 40° W. and S. 40° E.; desc. over NE. slope.
8.45	Head of ravine, drains E.; asc. over SE. slope.
12.60	Spur, slopes N. 40° E.; desc. over NW. slope.
18.85	Spur, slopes N. 10° W.; desc. 50 ft. over NE. slope.
20.28	Point for the SE 1/16 sec. cor. of sec. 24, at intersection with the E. and W. center line of the SE 1/4.
Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.	
SE 1/16 S 24 1982	
from which	
A hemlock, 8 ins. diam., bears N. 50 1/2° E., 17 1/2 lks. dist., mkd. SE 1/16 S24 BT.	
A fir, 54 ins. diam., bears N. 52° W., 25 lks. dist., mkd. SE 1/16 S24 BT.	
Descend over NE. slope.	
23.60	Creek, 15 lks. wide, course E.; asc. over broken S. slope.
40.55	The center E 1/16 sec. cor. of sec. 24.
From the S 1/16 sec. cor. of sec. 24 only, on the E. bdy. of the Tp., hereinbefore described.	
N. 88° 56' W., on the E. and W. center line of the SE 1/4 of sec. 24.	
Ascend along broken S. slope.	