

County Surveyor's Record, Douglas County, Oregon

17487

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

A madrone, 8 ins. diam., bears S. 84° W.,
54 lks. dist., with fragmentary scribe marks
visible on partially healed blaze.

A live oak, 7 ins. diam., bears N. 73° W.,
24 1/2 lks. dist., with scribe marks 1S R5W S16 BT
visible on partially healed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with aluminum cap mkd.

T 31 S R 5 W

S 16	S 15
S 21	S 22

1982

*FD OK.
B. SHAWER
6/92 M12-49*

Deposit the original stone alongside the aluminum post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, yew, alder, oak, chinquapin,
ash, madrone, and willow; undergrowth, poison oak, ferns,
salal, Oregon grape, salmonberry, arrowwood, wild rose,
blackberry, huckleberry, thimbleberry, hazel, and young
timber.

N. 0° 43' E., bet. secs. 15 and 16.

Ascend broken SE. slope, through heavy timber and dense
undergrowth.

15.30 Spur, slopes S. 75° E.; asc. broken SE. slope.

25.90 Spur, slopes E.; desc. NE. slope.

38.91 The 1/4 sec. cor. of secs. 15 and 16, perpetuated and
recorded by John M. Powell, Deputy County Surveyor, in
1966, monumented with an iron post, 1 1/4 ins. diam., firmly
set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

	T 31 S	
1/4	S 16	S 15
	R 5 W	

1966

from which the remaining original bearing tree

A fir, 47 ins. diam., bears N. 40° W., 6 lks.
dist., with scribe marks 1/4 S visible on bark
blaze, rescribed by Powell with fragmentary
scribe marks visible on partially healed blaze.

and a bearing tree mkd. by Powell

A fir, 16 ins. diam., bears N. 67° E.,
33 1/2 lks. dist., with healed double blaze.