

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, **17488**
 T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

Land, mountainous.
 Soil, rocky clay.
 Timber, fir, cedar, hemlock, yew, oak, madrone, alder,
 and chinquapin; undergrowth, poison oak, hazel, wild
 rose, huckleberry, salmonberry, arrowwood, thimbleberry,
 salal, Oregon grape, and young timber.

From the cor. of secs. 20, 21, 28, and 29, perpetuated
 and recorded by Arthur Boyer, Registered Engineer No.
 1581, in 1938, further perpetuated and recorded by Victor
 S. King, Registered Land Surveyor No. 442, in 1959,
 monumented with an iron rod, 1 1/4 ins. diam., firmly set,
 projecting 4 ins. above ground, from which the remains of
 the original bearing trees

A madrone, 24 ins. diam., bears S. 60° E.,
 28 lks. dist., rescribed by King, with scribe
 marks T31S R5W BT visible on partially healed
 blaze.

A maple rootcrown, size indeterminate, bears
 N. 34° W., 43 lks. dist., no marks visible.

and bearing trees mkd. by King

A yew, 16 ins. diam., bears N. 43 1/2° E.,
 65 1/2 lks. dist., with scribe marks S21 T31S
 R5W BT visible on open blaze.

A yew, 20 ins. diam., bears S. 42° W., 95 lks.
 dist., with fragmentary scribe marks visible
 on partially healed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam.,
 22 ins. in the ground directly over the iron rod, with
 aluminum cap mkd.

T 31 S	R 5 W
S 20	S 21
S 29	S 28

1982

from which a new bearing tree

A fir, 8 ins. diam., bears N. 28 1/2° W., 25 lks.
 dist., mkd. T31S R5W S20 BT.

N. 0° 7' E., bet. secs. 20 and 21.

Descend broken NE. slope through scattering timber and
 dense undergrowth.

15.45 West Fork Canyon Creek, 15 lks. wide, course E.; asc.
 broken SW. slope.

19.30 Gravelled road, 25 lks. wide, bears N. 35° W. and
 S. 55° E., in a curve.

40.15 Point for the 1/4 sec. cor. of secs. 20 and 21, at propor-
 tionate distance; there is no remaining evidence of the
 original corner.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam.,
 24 ins. in the ground, with aluminum cap mkd.