

# County Surveyor's Record, Douglas County, Oregon

**17489** Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

T 31 S    R 5 W  
          1/4  
S 20    |    S 21  
          |  
          1982

from which

A fir, 8 ins. diam., bears N. 67° E., 73 lks.  
dist., mkd. 1/4 S21 BT.

A fir, 5 ins. diam., bears S. 48 1/2° W., 5 1/2 lks.  
dist., mkd. 1/4 S20 BT.

Ascend broken SW. slope.

60.225

Point for the N 1/16 sec. cor. of secs. 20 and 21.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

N 1/16  
S 20    |    S 21  
          |  
          1982

FD BC+1 BT  
2 NEW BTs  
R QUIMBY  
2/2020  
CS65/104-48

from which

A cedar, 12 ins. diam., bears N. 53 3/4° E.,  
49 lks. dist., mkd. N 1/16 S21 BT.

A fir, 5 ins. diam., bears N. 88 1/4° W.,  
7 1/2 lks. dist., mkd. X BT.

Ascend broken SW. slope.

62.15

Dirt road, 20 lks. wide, bears E. and S. 35° W.

73.15

Ridge, bears N. 80° E. and S. 80° W.; desc. NW. slope.

80.30

The cor. of secs. 16, 17, 20, and 21, perpetuated and recorded by Victor S. King, Registered Land Surveyor No. 442, in 1959, further perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S    R 5 W  
S 17    |    S 16  
S 20    |    S 21  
          |  
          1966

from which the remains of an original bearing tree

A decayed fir stump, size indeterminate, bears  
N. 64° E., 43 lks. dist., no marks visible.

and bearing trees mkd. by King

A fir, 15 ins. diam., bears N. 56° E., 15 lks.  
dist., with healed blaze.

A fir, 12 ins. diam., bears S. 83° E., 58 1/2  
lks. dist., with healed blaze.