

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, **17494**  
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
10.05	Spur, slopes N. 75° E.; desc. broken NE. slope.
28.65	West Fork of Canyon Creek, 15 lks. wide, course N. 85° E.; asc. broken SW. slope.
34.90	Gravelled road, 20 lks. wide, bears N. 70° W. and S. 70° E.
39.65	<p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 31 S    R 5 W</p> <p>      1/4</p> <p>       </p> <p>S 19         S 20</p> <p>      1982</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears N. 36° E., 10 lks. dist., mkd. 1/4 S20 BT.</p> <p style="margin-left: 40px;">A grand fir, 12 ins. diam., bears N. 53° W., 10 1/2 lks. dist., mkd. 1/4 S19 BT.</p> <p>From this point, United States Coast and Geodetic Survey triangulation station SILVER BUTTE 1942, bears S. 85° 57' W., 209.94 chs. dist., monumented with a standard brass tablet, 3 1/2 ins. diam., firmly set in bedrock, 12 ins. below ground surface, mkd. SILVER BUTTE 1942, and a triangle.</p> <p>Ascend broken SW. slope.</p>
52.50	Dirt road, 15 lks. wide, bears N. 80° W. and S. 80° E.
59.475	<p>Point for the N 1/16 sec. cor. of secs. 19 and 20.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>N 1/16</p> <p>       </p> <p>S 19         S 20</p> <p>      1982</p> </div> <div style="float: right; text-align: right; margin-top: 10px;"> <p><i>BC</i> Referenced out &amp; reset D. Edwards 7/20 22 Fd 2 BTs set 2 steel posts CS 65/109-60</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears S. 38 1/4° E., 19 lks. dist., mkd. N 1/16 S20 BT.</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears N. 37 1/2° W., 53 lks. dist., mkd. N 1/16 S19 BT.</p> <p>Ascend broken SW. slope.</p>
76.55	Spur, slopes S. 80° W.; desc. NW. slope.
77.95	Dirt road, 25 lks. wide, bears N. 70° E. and S. 70° W.
79.30	The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.