

County Surveyor's Record, Douglas County, Oregon

17495

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

T 31 S R 5 W

S 18	S 17
S 19	S 20

1966

from which the remaining original bearing tree

A fir, 45 ins. diam., bears N. 18° E., 33 lks. dist., with fragmentary scribe marks visible on opened blaze, remarked T31S R5W S17 BT RS 442 on bark blaze by Victor S. King, Registered Land Surveyor No. 442, in 1959.

and bearing trees mkd. by Victor S. King, Registered Land Surveyor No. 442, in 1959

A white fir, 15 ins. diam., bears S. 72° E., 19 1/2 lks. dist., with healed blaze.

A white fir, 18 ins. diam., bears N. 40° W., 10 lks. dist., with healed blaze.

and bearing trees mkd. by John M. Powell, Deputy County Surveyor, in 1966

A white fir, 16 ins. diam., bears N. 51° E., 63 lks. dist., with healed blaze.

A white fir, 22 ins. diam., bears S. 83° W., 56 1/2 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, pine, yew, hemlock, alder, oak, ash, willow, madrone, maple, and chinquapin; undergrowth; poison oak, blackberry, salal, Oregon grape, salmon-berry, arrowwood, hazel, huckleberry, wild rose, manzanita, ceanothus, ferns, and young timber.

From the cor. of secs. 16, 17, 20, and 21.

S. 89° 08' W., bet. secs. 17 and 20.

Descend along ridge top over NW. slope, through heavy timber and dense undergrowth.

12.75 Ridge, bears N. 30° W. and S. 30° E.; desc. SW. slope.

30.05 Ravine, drains S. 20° E.; asc. broken SE. slope.

38.75 Spur, slopes S. 10° W.; asc. SE. slope.

39.28 Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 31 S R 5 W

1/4	S 17	
	S 20	

1982