

County Surveyor's Record, Douglas County, Oregon

17501 Dependent Resurvey of a Portion of the East Boundary,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

Beginning at the cor. of secs. 1, 6, 7, and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 27 S
R 3 W R 2 W
S 1 | S 6
S 12 | S 7
1958

from which the remains of bearing trees mkd. by Corbin

A fir, 13 ins. diam., bears S. 55° E., 95 lks. dist., with healed blaze.

A sawed fir stump, 24 ins. diam., bears S. 60° W., 36 lks. dist., with healed blaze.

and a bearing tree mkd. by Rogers

A pine, 34 ins. diam., bears N. 15° W., 61 lks. dist., with scribe marks T27S R3W S1 BT visible on open blaze.

and new bearing trees

A fir, 13 ins. diam., bears N. 12° E., 220 lks. dist., mkd. T27S R2W S6 BT.

A fir, 4 ins. diam., bears S. 22 1/2° W., 30 1/2 lks. dist., mkd. X BT.

N. 1° 53' E., bet. secs. 1 and 6, marking and blazing the true line.

Ascend over broken SE. slope, changing to SW. slope, through heavy timber and dense undergrowth.

20.19

Point for the S 1/16 sec. cor. of secs. 1 and 6.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

S 1/16
S 1 | S 6
1982

from which

A fir, 5 ins. diam., bears N. 56° E., 76 lks. dist., mkd. S 1/16 S6 BT.

A fir, 9 ins. diam., bears S. 83 1/4° W., 82 lks. dist., mkd. S 1/16 S1 BT.

Ascend over broken SW. slope.

40.38

The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 27 S
1/4
R 3 W R 2 W
S 1 | S 6
1958

from which the remains of an original bearing tree