County Surveyor's Record, Douglas County, Oregon

17503 Dependent Resurvey of a Portion of the North Boundary, T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
6.50	Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.
19.06	Point for the W 1/16 sec. cor. of secs. 1 and 36.
	Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	W 1/16 $\frac{\text{S 36}}{\text{S 1}}$ 1982
	from which
	A fir, 11 ins. diam., bears N. 7 1/2° E., 47 lks. dist., mkd. W 1/16 S36 BT.
	A fir, 8 ins. diam., bears S. 36 1/2° E., 21 lks. dist., mkd. W 1/16 S1 BT.
27.30	Spur, slopes S. 10° E.; desc. over SW. slope.
38.12	The cor. of secs. 1, 2, 35, and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.
	T 26 S R 3 W S 35 | S 36 S 2 | S 1 T 27 S 1958
	from which the remains of the bearing trees mkd. by Arthur Boyer, Deputy County Surveyor, in 1936
	A root hole, bears N. 11° E., 2 1/2 lks. dist., with a down fir alongside, 14 ins. diam., with fragmentary scribe marks visible on decayed blaze.
	A sawed fir stump, 24 ins. diam., bears S. 34° E., 34 lks. dist., with healed blaze.
	A fir snag, 14 ins. diam., bears S. 72° W., 29 lks. dist., with healed blaze.
	A sawed fir stump, 14 ins. diam., bears N. 36° W., 12 lks. dist., with healed blaze.
	and the remains of bearing trees mkd. by Corbin
	A sawed fir stump, 23 ins. diam., bears N. 51 1/2° E., 63 lks. dist., with healed blaze.
	A cedar, 21 ins. diam., bears S. 73 1/4° E., 84 lks. dist., with healed blaze.
	and a bearing tree mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1966
	A sawed cedar stump, 24 ins. diam., bears N. 48° W., 38 lks. dist., with healed blaze.
	and a bearing tree mkd . by Rogers
	A cedar, 20 ins. diam., bears S. 61 3/4° W., 25 1/2 lks. dist., with scribe marks T27S R3W S2 BT visible on partially healed blaze.
	and new bearing trees