

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the North Boundary **17504**  
T. 27 S., R. 3 W., Willamette Meridian, Oregon

**CHAINS**

A fir, 6 ins. diam., bears N. 71 1/4° E., 33 1/2 lks. dist., mkd. T26S R3W S36 BT.

A maple, 7 ins. diam., bears N. 32 1/2° W., 45 1/2 lks. dist., mkd. T26S R3W S35 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, pine, alder, madrone, oak, maple, willow, and ash; undergrowth, poison oak, hazel, wild rose, blackberry, huckleberry, salal, arrowwood, fern, vine maple, and young timber.

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 27 S., R. 3 W.,  
Willamette Meridian, Oregon

(Retracing the survey by Addison R. Flint and  
L. L. Williams in 1871, the survey by Samuel C. Flint  
in 1882, and the resurvey by Harold D. Corbin in 1958

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp.

S. 89° 19' W., bet. secs. 1 and 12, marking and blazing the true line.

Ascend over broken SE. slope, through heavy timber and dense undergrowth.

3.25 Spur, slopes S.; desc. over SW. slope.

10.65 Creek, 3 lks. wide, course SW.; asc. over SE. slope.

19.12 The E 1/16 sec. cor. of secs. 1 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

E 1/16  $\frac{S 1}{S 12}$   
1958

from which bearing trees mkd. by Corbin

A fir, 7 ins. diam., bears S. 74 1/2° E., 12 lks. dist., with scribe marks 1/16 S12 BT visible on open blaze.

A fir, 20 ins. diam., bears N. 58 1/2° W., 39 lks. dist., with healed blaze.

S. 89° 18' W., beginning new measurement.

Ascend over broken SE. slope.

1.80 Spur, slopes S.; desc. over broken SW. slope.

19.10 The 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

T 27 S R 3 W  
1/4  $\frac{S 1}{S 12}$   
1958

FD. OK D. EDWARDS  
M150-40 3/2006