

County Surveyor's Record, Douglas County, Oregon

17505

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A sawed cedar stump, 36 ins. diam., bears S. 25° E.,
28 lks. dist., no marks visible. (Record, 25
lks.)

A sawed cedar stump, 36 ins. diam., bears N. 60° W.,
60 lks. dist., no marks visible. (Record, 64
lks.)

and bearing trees mkd. by Corbin

A fir, 12 ins. diam., bears N. 43 1/4° E., 92 lks.
dist., with healed blaze.

A grand fir, 14 ins. diam., bears S. 44° E.,
100 lks. dist., with healed blaze.

and new bearing trees

A fir, 8 ins. diam., bears N. 4 1/2° W., 19 lks.
dist., mkd. 1/4 S1 BT.

A fir, 14 ins. diam., bears S. 30 1/2° E., 27 lks.
dist., mkd. 1/4 S12 BT.

N. 89° 20' W., beginning new measurement.

Descend over SW. slope.

1.80 Creek, 7 lks. wide, course S. 5° W.; asc. over broken SE.
slope.

11.00 Spur, slopes S. 20° W.; desc. over SW. slope.

19.42 The W 1/16 sec. cor. of secs. 1 and 12, monumented with
an iron post, 2 1/2 ins. diam., firmly set, projecting 4
ins. above ground, with brass cap mkd.

W 1/16 $\frac{S 1}{S 12}$
1958

from which bearing trees mkd. by Corbin

A fir, 20 ins. diam., bears S. 23 3/4° E., 103
lks. dist., with healed blaze.

A fir, 22 ins. diam., bears N. 60 1/2° W., 270 lks.
dist., with scribe marks W 1/16 S visible on
partially healed blaze. (Record, N. 59 1/2° W.,
272 lks.)

and new bearing trees

A fir, 19 ins. diam., bears N. 40 1/4° E., 54 1/2
lks. dist., mkd. W 1/16 S1 BT.

A fir, 12 ins. diam., bears S. 50° E., 73 lks.
dist., mkd. W 1/16 S12 BT.

N. 89° 15' W., beginning new measurement.

Descend over SW. slope.

17.85 Bond Creek, 5 lks. wide, course SW.; asc. over SE. slope.