

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 1,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

17510

<p>CHAINS 20.23</p>	<p>Point for the SE 1/16 sec. cor. of sec. 1, at intersection with the E. and W. center line of the SE 1/4.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">SE 1/16 S 1 1982</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 21° E., 32 lks. dist., mkd. SE 1/16 S1 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 81° W.; 24 1/2 lks. dist., mkd. SE 1/16 S1 BT.</p> <p>Ascend over SW. slope.</p>
<p>28.25</p> <p>40.47</p>	<p>Top of ascent, slopes W.; desc. NW. slope.</p> <p>The center E 1/16 sec. cor. of sec. 1.</p>
<p>8.05</p> <p>13.35</p> <p>19.47</p> <p>25.45</p> <p>29.90</p> <p>31.70</p> <p>38.93</p>	<p>From the S 1/16 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp.</p> <p>S. 89° 29' W., on the E. and W. center line of the SE 1/4 of sec. 1.</p> <p>Descend over broken SW. slope, through heavy timber and dense undergrowth.</p> <p>Creek, 2 lks. wide, course S. 5° E.; asc. over broken SE. slope.</p> <p>Spur, slopes S.; desc. over broken SW. slope.</p> <p>The SE 1/16 sec. cor. of sec. 1.</p> <p>Descend over broken SW. slope.</p> <p>Ravine, drains S.; asc. over broken SE. slope.</p> <p>Spur, slopes S. 10° W.; desc. over broken SW. slope.</p> <p>Creek, 2 lks. wide, course S. 10° W.; asc. over SE. slope.</p> <p>The center S 1/16 sec. cor. of sec. 1.</p>
<p>16.60</p> <p>18.50</p> <p>20.14</p>	<p>From the W 1/16 sec. cor. of secs. 1 and 12.</p> <p>N. 0° 07' W., on the N. and S. center line of the SW 1/4 of sec. 1.</p> <p>Ascend over SW. slope, through heavy timber and dense undergrowth.</p> <p>Spur, slopes N. 70° W.; desc. over NE. slope.</p> <p>Ravine, drains N. 65° W.; asc. over SW. slope.</p> <p>Point for the SW 1/16 sec. cor. of sec. 1, at intersection with the E. and W. center line of the SW 1/4.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>

Fr. 08 4/10/82
 R. Carver
 C.S. 6/2/82