

County Surveyor's Record, Douglas County, Oregon

17516

Dependent Resurvey, Portion of W. Bdy.,
T. 25 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

N. 0° 06' W., beginning new measurement.

Descend over NW. slope.

2.45 Ravine, drains W.; asc. over SW. slope.

4.55 Spur, slopes NW.; desc. over N. slope.

19.77 The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 25 S
1/4
R 5 W | R 4 W
S 24 | S 19
1957

from which the remaining original bearing tree

A white oak, 24 ins. diam., bears S. 19° E., 98 lks. dist., with scribe marks BT visible on opened blaze.

and the remains of the bearing trees mkd. in 1957

A fir, 19 ins. diam., bears S. 82 1/2° E., 67 lks. dist., with healed blaze. (Record, S. 81° E.)

A sawed fir stump, 18 ins. diam., bears S. 70 1/4° W., 30 1/2 lks. dist., with healed blaze.

and a new bearing tree

A fir, 8 ins. diam., bears S. 56 1/2° W., 34 1/2 lks. dist., mkd. 1/4 S24 BT.

Land, rolling hills.

Soil, sandy clay.

Timber, oak, fir, cedar, maple, yew, madrone, pine, ash, willow, alder, and cottonwood; undergrowth, poison oak, fern, blackberry, huckleberry, thimbleberry, arrowwood, hazel, salal, vine maple, and young timber.

Dependent Resurvey of a Portion of the
Subdivisional Lines, T. 25 S., R. 4 W.,
Willamette Meridian, Oregon

(Restoring the 1855-56 survey by Harvey Gordon and Charles T. Gardner, the 1871 survey by William H. Byars, and the 1957-58 resurvey by Irving Zirpel, Jr., Lynn M. Roseberry, and Harold D. Corbin)

From the cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 25 S R 4 W
S 29 | S 28
S 32 | S 33
1957

from which the remains of the original bearing trees

A fir rootcrown, 30 ins. diam., bears N. 72 1/2° E., 30 lks. dist., no marks remain.