

County Surveyor's Record, Douglas County, Oregon

17519 Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
19.43	<p>The E 1/16 sec. cor. of secs. 29 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S\ 29}{S\ 32}$ 1957</p> <p>from which the remains of the bearing trees mkd. in 1957</p> <p style="padding-left: 40px;">A root hole, bears N. 54° E., 40 1/2 lks. dist., with an uprooted fir alongside, 22 ins. diam., with fragmentary scribe marks visible on open blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 30 3/4° E., 58 lks. dist., with healed blaze. (Record, 61 lks.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 41° W., 153 lks. dist., mkd. E 1/16 S29 BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 88° 52' W., beginning new measurement.</p> <p>Ascend over E. slope.</p>
3.20	Gravelled road, 15 lks. wide, bears N. 10° E. and S. 20° W.
5.65	Spur, slopes N., and a gravelled road, 15 lks. wide, bears N. and S.; desc. over W. slope, changing to SW. slope.
16.60	Three wire transmission line, bears N. 15° E. and S. 15° W.
19.48	<p>The 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 S R 4 W 1/4 $\frac{S\ 29}{S\ 32}$ 1957</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir snag, 35 ins. diam., bears N. 39 1/4° E., 32 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A root hole, bears S. 40° W., 23 lks. dist., with an uprooted cedar alongside, 33 ins. diam., with healed blaze. (Record, S. 40° E.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A madrone, 5 ins. diam., bears S. 40 1/4° W., 13 1/2 lks. dist., mkd. 1/4 S32 BT in the bark.</p> <p>No other suitable trees available.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 87° 01' W., beginning new measurement.</p> <p>Descend over broken SW. slope.</p>