

County Surveyor's Record, Douglas County, Oregon

17521 Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>Timber, fir, cedar, madrone, oak, ash, yew, hemlock, maple, alder, and chinquapin; undergrowth, poison oak, hazel, fern, salal, vine maple, blackberry, arrowwood, and young timber.</p>
19.99	<p>N. 4° 24' W., bet. secs. 29 and 30.</p> <p>Descend over N. slope, changing to NE. slope, through scattering timber and dense undergrowth.</p> <p>The S 1/16 sec. cor. of secs. 29 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 1/16 S 30 S 29 1957</p> </div> <p>from which the remains of bearing trees mkd. in 1957</p> <p style="margin-left: 40px;">A maple, 17 ins. diam., bears S. 88 1/2° E., 50 lks. dist., with healed blaze. (Record, 48 lks.)</p> <p style="margin-left: 40px;">A sawed fir stump, 13 ins. diam., bears S. 37 3/4° W., 108 lks. dist., with healed blaze.</p> <p>and new bearing trees</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears S. 86° E., 40 lks. dist., mkd. S 1/16 S29 BT.</p> <p style="margin-left: 40px;">A fir, 7 ins. diam., bears S. 44° W., 27 1/2 lks. dist., mkd. S 1/16 S30 BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 4° 29' W., beginning a new measurement.</p> <p>Descend over NE. slope.</p>
13.35	<p>Creek, 5 lks. wide, course N. 30° W.; asc. over SW. slope.</p>
20.02	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 25 S R 4 W 1/4 S 30 S 29 1957</p> </div> <p>from which the bearing trees mkd. in 1957</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears S. 27 1/2° E., 35 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears N. 27 1/4° W., 7 lks. dist., with healed blaze.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 4° 23' W., beginning a new measurement.</p> <p>Descend over NW. slope.</p>
4.55	<p>Gravelled road, 20 lks. wide, bears N. 50° E. and S. 50° W.</p>