

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17526**
T. 25 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

10.00 Spur, slopes NW.; desc. over broken N. slope.

33.70 Creek, 3 lks. wide, course W.; asc. over S. slope.

39.74 The 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 25 S R 4 W
1/4
S 19 | S 20
1957

from which the remaining original bearing tree

A fir, 40 ins. diam., bears S. 19° W., 14 lks. dist., with healed blaze.

and a bearing tree mkd. by Wilford N. Haines, Registered Land Surveyor No. 239, in 1956

A fir, 29 ins. diam., bears S. 76 1/4° E., 62 lks. dist., with healed blaze. (Record, S. 70° E.)

and bearing trees mkd. in 1957

A fir, 18 ins. diam., bears S. 30° E., 40 lks. dist., with healed blaze.

A fir, 39 ins. diam., bears S. 34° W., 32 lks. dist., with healed blaze.

N. 1° 24' E., beginning new measurement.

Ascend over S. slope.

10.60 Ridge, bears E. and W.; desc. over N. slope.

20.18 The N 1/16 sec. cor. of secs. 19 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

N 1/16
S 19 | S 20
1957

from which the remains of a bearing tree mkd. in 1957

A sawed fir stump, 48 ins. diam., bears N. 30 1/4° W., 94 lks. dist., with healed blaze.

and a bearing tree mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1965

A fir, 6 ins. diam., bears S. 72° E., 19 lks. dist., with healed double blaze.

and a new bearing tree

A fir, 6 ins. diam., bears S. 59 1/2° W., 48 lks. dist., mkd. N 1/16 S19 BT.

N. 1° 47' E., beginning new measurement.

Descend over N. slope.