

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17528**
T. 25 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">A fir, 29 ins. diam., bears S. 44 3/4° E., 124 1/2 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1965</p> <p style="text-align: center;">A fir, 16 ins. diam., bears N. 18° E., 152 lks. dist., with healed blaze.</p> <p>and new bearing trees</p> <p style="text-align: center;">A fir, 17 ins. diam., bears S. 45 1/2° W., 81 1/2 lks. dist., mkd. E 1/16 S19 BT.</p> <p style="text-align: center;">A fir, 13 ins. diam., bears N. 55° W., 62 lks. dist., mkd. E 1/16 S18 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">S. 89° 31' W., beginning new measurement.</p> <p>Descend over broken SW. slope.</p>
19.98	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 25 S R 4 W 1/4 $\frac{S\ 18}{S\ 19}$ 1957</p> </div> <p>from which bearing trees mkd. in 1957</p> <p style="text-align: center;">A white oak, 14 ins. diam., bears N. 41 1/2° E., 163 lks. dist., with healed blaze.</p> <p style="text-align: center;">A fir, 11 ins. diam., bears S. 57° E., 46 1/2 lks. dist., with healed blaze.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, oak, cedar, hemlock, yew, madrone, ash, maple, and chinquapin; undergrowth, huckleberry, poison oak, salal, fern, arrowwood, hazel, blackberry, salmonberry, wild rose, and young timber.</p>
<p>Subdivision of Section 19, T. 25 S., R. 4 W., Willamette Meridian, Oregon</p>	
1.50	<p>From the 1/4 sec. cor. of secs. 19 and 30.</p> <p>N. 0° 44' E., on the N. and S. center line of sec. 19.</p> <p>Ascend over SE. slope, through heavy timber and dense undergrowth.</p> <p>Spur, slopes E.; desc. over NE. slope.</p>
6.05	<p>Gravelled road, 30 lks. wide, bears N. 55° W. and S. 40° E., in a curve.</p>
15.90	<p>Sutherlin Creek, 12 lks. wide, course N. 70° W.; asc. over SW. slope.</p>
17.50	<p>Dirt road, 15 lks. wide, bears N. 30° W. and S. 45° E.</p>