

County Surveyor's Record, Douglas County, Oregon

17529

Subdivision of Section 19,
T. 25 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
20.03	<p>The center S 1/16 sec. cor. of sec. 19, established and recorded by Victor M. McLind, Registered Land Surveyor No. 934, in 1971, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, from which a bearing tree mkd. by McLind</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 62 1/4° E., 37 1/2 lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} C \\ S\ 1/16 \quad \quad S\ 19 \\ C \\ 1982 \end{array}$ </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 53 1/2° W., 60 lks. dist., mkd. CS 1/16 S19 BT.</p> <p style="padding-left: 40px;">Reset the iron rod alongside the iron post.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 44' E., beginning new measurement.</p> <p>Ascend over SW. slope.</p>
1.60	Spur, slopes W.; desc. over NW. slope.
15.90	Spur, slopes S. 35° W.; desc. over NW. slope.
20.03	<p>Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E. and W. center line.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} T\ 25\ S\ R\ 4\ W \\ C\ 1/4\ S\ 19 \\ 1982 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 51° E., 34 1/2 lks. dist., mkd. C 1/4 S19 BT.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 17 1/4° E., 59 1/2 lks. dist., mkd. C 1/4 S19 BT.</p> <p>Descend over NW. slope.</p>
22.30	Ravine, drains S. 50° W.; asc. over SW. slope.
34.20	Ridge, bears N. 80° E. and N. 65° W.; desc. over NE. slope.
40.25	<p>The center N 1/16 sec. cor. of sec. 19, established and recorded by Victor M. McLind, Registered Land Surveyor No. 934, in 1971, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, from which a bearing tree mkd. by McLind</p>