

County Surveyor's Record, Douglas County, Oregon

17533

Subdivision, Section 29,
T. 25 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 S R 4 W C 1/4 S 29 1982</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears N. 61° E., 18 lks. dist., mkd. C 1/4 S29 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 33° W., 55 1/2 lks. dist., mkd. C 1/4 S29 BT.</p> <p>Descend over NW. slope.</p>
40.25	Ravine, drains W.; asc. over SW. slope.
42.45	Spur, slopes W.; desc. over broken NW. slope.
49.20	Spur, slopes W.; desc. over NW. slope.
56.25	Ravine, drains N. 70° W.; asc. over SW. slope.
57.32	<p>Point for the center N 1/16 sec. cor. of sec. 29.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 29 C 1982</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 25 ins. diam., bears N. 79° E., 30 1/2 lks. dist., mkd. CN 1/16 S29 BT.</p> <p style="padding-left: 40px;">A cedar, 13 ins. diam., bears N. 17 1/2° W., 68 lks. dist., mkd. CN 1/16 S29 BT.</p> <p>Descend over broken NW. slope.</p>
62.15	Dirt road, 15 lks. wide, bears E. and W.
73.90	Enter swampy area, edge bears E. and W.
75.45	Sutherlin Creek, 3 lks. wide, course S. 50° W.; continue across swampy area.
76.65	Leave swampy area, edge bears E. and W.; asc. over SE. slope.
76.92	The 1/4 sec. cor. of secs. 20 and 29.
	<p>From the 1/4 sec. cor. of secs. 28 and 29.</p> <p>N. 89° 43' W., on the E. and W. center line of sec. 29.</p> <p>Descend over NW. slope, through heavy timber and dense undergrowth.</p>
15.75	Gravelled road, 20 lks. wide, bears N. 40° W. and S. 50° E.
19.28	Point for the center E 1/16 sec. cor. of sec. 29.