

County Surveyor's Record, Douglas County, Oregon

Subdivision, Section 29,
T. 25 S., R. 4 W., Willamette Meridian, Oregon

17534

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C $\frac{E \ 1/16}{S \ 29}$ C 1982</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 11 ins. diam., bears N. 20° E., 19 1/2 lks. dist., mkd. CE 1/16 S29 BT.</p> <p style="padding-left: 40px;">A grand fir, 10 ins. diam., bears S. 23 1/4° E., 57 1/2 lks. dist., mkd. CE 1/16 S29 BT.</p> <p>Descend over NW. slope.</p>
32.35	Three wire transmission line, bears N. 5° W. and S. 5° E.
33.10	Dirt road, 15 lks. wide, bears N. and S.
33.50	Ridge, bears N. and S.; desc. over broken NW. slope.
38.56	The center 1/4 sec. cor. of sec. 29.
	Descend over broken W. slope.
59.48	Point for the center W 1/16 sec. cor. of sec. 29.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C $\frac{W \ 1/16}{S \ 29}$ C 1982</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 9 1/2° E., 27 lks. dist., mkd. CW 1/16 S29 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 15 1/2° E., 31 1/2 lks. dist., mkd. CW 1/16 S29 BT.</p> <p>Descend over NW. slope.</p>
62.55	Creek, 5 lks. wide, course N. 30° W.; asc. over NE. slope.
72.85	Spur, slopes N. 20° W.; desc. over broken NW. slope.
80.40	The 1/4 sec. cor. of secs. 29 and 30.
	<p>From the E 1/16 sec. cor. of secs. 29 and 32.</p> <p>N. 4° 16' W., on the N. and S. center line of the SE 1/4 of sec. 29.</p> <p>Ascend over broken SE. slope, through heavy timber and dense undergrowth.</p>
3.30	Dirt road, 15 lks. wide, bears N. 55° E. and S. 55° W.
7.30	Spur, slopes E.; desc. over NE. slope.
19.01	Point for the SE 1/16 sec. cor. of sec. 29, at intersection with the E. and W. center line of the SE 1/4 of sec. 29.