

# County Surveyor's Record, Douglas County, Oregon

17535

Subdivision, Section 29,  
T. 25 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
38.04	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 29 1982</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 11 ins. diam., bears N. 30 1/2° E., 35 1/2 lks. dist., mkd. SE 1/16 S29 BT.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 54 1/4° W., 57 lks. dist., mkd. SE 1/16 S29 BT.</p> <p>Descend over NE. slope.</p> <p>The center E 1/16 sec. cor. of sec. 29.</p>
8.05	<p>From the S 1/16 sec. cor. of secs. 28 and 29.</p> <p>S. 89° 15' W., on the E. and W. center line of the SE 1/4 of sec. 29.</p> <p>Descend over NW. slope, through heavy timber and dense undergrowth.</p> <p>Gravelled road, 20 lks. wide, bears N. 25° W. and S. 25° E.</p>
19.34	<p>The SE 1/16 sec. cor. of sec. 29.</p> <p>Ascend over broken NE. slope.</p>
32.40	<p>Ridge, bears N. 10° W. and S. 10° E.; desc. over NW. slope.</p>
32.70	<p>Three wire transmission line, bears N. 5° W. and S. 5° E.</p>
33.35	<p>Dirt road, 15 lks. wide, bears N. 10° E. and S. 10° W.</p>
38.72	<p>The center S 1/16 sec. cor. of sec. 29.</p>
0.30	<p>From the W 1/16 sec. cor. of secs. 29 and 32.</p> <p>N. 4° 13' W., on the N. and S. center line of the SW 1/4 of sec. 29.</p> <p>Descend over N. slope, through scattering timber and dense undergrowth.</p> <p>Creek, 5 lks. wide, course N. 20° E.; desc. along creek bottom.</p>
1.85	<p>Creek, 5 lks. wide, course N. 40° W.; desc. over broken NW. slope.</p>
19.47	<p>Point for the SW 1/16 sec. cor. of sec. 29, at intersection with the E. and W. center line of the SW 1/4 of sec. 29.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">SW 1/16 S 29 1982</p>