

County Surveyor's Record, Douglas County, Oregon

Subdivision, Section 29,
T. 25 S., R. 4 W., Willamette Meridian, Oregon 17538

CHAINS	
22.25	<p>from which</p> <p style="margin-left: 40px;">A cedar, 10 ins. diam., bears N. 73 1/2° E., 77 1/2 lks. dist., mkd. SW 1/16 S29 BT.</p> <p style="margin-left: 40px;">A fir, 18 ins. diam., bears N. 22 1/2° W., 111 lks. dist., mkd. SW 1/16 S29 BT.</p> <p>Descend over broken NW. slope.</p> <p>Creek, 5 lks. wide, course N. 5° W.; desc. along creek.</p>
23.00	<p>Leave creek, course N. 25° W.; desc. over broken NW. slope.</p>
38.91	<p>The center W 1/16 sec. cor. of sec. 29.</p>
20.81	<p>From the center S 1/16 sec. cor. of sec. 29.</p> <p>S. 88° 43' W., on the E. and W. center line of the SW 1/4 of sec. 29.</p> <p>Descend over broken NW. slope, through heavy timber and dense undergrowth.</p> <p>The SW 1/16 sec. cor. of sec. 29.</p>
21.30	<p>Descend over NW. slope.</p>
32.50	<p>Creek, 3 lks. wide, course N.; asc. over NE. slope.</p>
40.60	<p>Spur, slopes N.; desc. over broken NW. slope.</p>
41.60	<p>Creek, 2 lks. wide, course N.; asc. over NE. slope.</p>
7.30	<p>The S 1/16 sec. cor. of secs. 29 and 30.</p> <p>From the center W 1/16 sec. cor. of sec. 29.</p> <p>N. 4° 13' W., on the N. and S. center line of the NW 1/4 of sec. 29.</p> <p>Descend over NW. slope, through heavy timber and dense undergrowth.</p> <p>Ravine, drains S. 60° W.; asc. over broken SW. slope.</p>
14.40	<p>Dirt road, 20 lks. wide, bears N. 40° E. and S. 40° W.</p>
15.40	<p>Sutherlin Creek, 2 lks. wide, course S. 30° W.; asc. over broken SE. slope.</p>
19.85	<p>Point for the NW 1/16 sec. cor. of sec. 29, at intersection with the E. and W. center line of the NW 1/4 of sec. 29.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 29 1982</p> <p>from which</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears S. 70° E., 100 lks. dist., mkd. NW 1/16 S29 BT.</p>