

County Surveyor's Record, Douglas County, Oregon

17539

T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and the subdivision of section 14, Township 23 South, Range 4 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

A portion of the subdivisional lines was surveyed by Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, in 1855-56.

A portion of the subdivisional lines was surveyed by William P. Wright, U.S. Deputy Surveyor, in 1884.

The line between sections 13 and 14 was resurveyed by James E. Jelley, Cadastral Surveyor, in 1971.

A portion of the subdivisional lines was resurveyed by James E. Jelley, Cadastral Surveyor, in 1976.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated October 28, 1981, for Group No. 1083, Oregon.

The directions of the lines refer to the true meridian as determined by deflection angles turned from azimuths obtained by direct solar observations.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. The retrace-ment data were thoroughly verified and only the true line field notes are given herein. All lines not forming a closure were measured twice. Only those lines bounding or crossing public lands were blazed.

The geographic position of the corner of sections 23, 24, 25, and 26, as scaled from the quadrangle map, "ANLAUF, OREGON," published by the United States Geological Survey in 1954, is as follows:

Latitude 43° 32.9' N. Longitude 123° 07.6' W.

The mean magnetic declination is 19° 00' E.

Dependent Resurvey of
a Portion of the Subdivisional Lines,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

(Restoring the survey
by Harvey Gordon and Charles T. Gardner in 1855-56,
the survey by William P. Wright in 1884,
the resurvey by James E. Jelley in 1971, and
the resurvey by James E. Jelley in 1976)

Beginning at the cor. of secs. 13, 14, 23, and 24, monu-
mented with an iron post, 2 1/2 ins. diam., firmly set,
projecting 4 ins. above ground, with brass cap mkd.