

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, **17542**  
T. 23 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

- 4.00 Gravelled road, 20 lks. wide, bears N. 25° W. and S. 30° E.
- 39.21 The 1/4 sec. cor. of secs. 23 and 26, reestablished at proportionate distance by Wilford N. Haines, Registered Land Surveyor No. 239, during an unrecorded survey, date unknown, and is accepted as the best available evidence of the position of the original corner, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 9 ins. above ground, with a steel washer, 1 in. diam., mkd. Wilford N. Haines 239 Survey Point Drain Ore.
- At the corner point
- Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
- T 23 S R 4 W
- 1/4  $\frac{S\ 23}{S\ 26}$
- 1982
- from which
- A fir, 13 ins. diam., bears N. 34° E., 10 lks. dist., mkd. 1/4 S23 BT.
- A fir, 10 ins. diam., bears S. 60° W., 15 lks. dist., mkd. 1/4 S26 BT.
- 
- N. 89° 41' W., beginning new measurement.
- Descend over SW. slope, changing to NW. slope.
- 14.10 Creek, 30 lks. wide, course N. 40° W.; asc. over NE. slope.
- 35.75 Spur, slopes N. 20° E.; desc. over NW. slope.
- 38.20 Creek, 4 lks. wide, course N. 55° E.; asc. over SE. slope.
- 39.21 The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
- T 24 S R 4 W
- |      |      |
|------|------|
| S 22 | S 23 |
| S 27 | S 26 |
- 1976
- from which the remains of an original bearing tree
- A fir snag, 65 ins. diam., bears S. 25° E., 96 lks. dist., with scribe marks T23S R4W S2 BT visible on bark blaze.
- and the remains of bearing trees mkd. by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1960
- A sawed fir stump, 36 ins. diam., bears S. 89° W., 67 lks. dist., with scribe marks BT visible on bark blaze.