

County Surveyor's Record, Douglas County, Oregon

431

17545

Subdivision of Section 14,
T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir, 6 ins. diam., bears N. 88 1/2° E., 69 1/2 lks. dist., mkd. CS 1/16 S14 BT.

A hemlock, 7 ins. diam., bears S. 8° W., 35 lks. dist., mkd. CS 1/16 S14 BT.

Descend over NW. slope.

20.10 Ravine, drains W.; asc. over broken SW. slope.

33.50 Ridge, bears N. 30° W. and S. 30° E.; desc. over NE. slope.

39.88 Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line of sec. 14.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

ENO. OK 6/91
D. PEEL M 1/13-42

T 23 S R 4 W
C 1/4 S 14
1982

from which

A fir, 8 ins. diam., bears N. 86 1/4° E., 17 1/2 lks. dist., mkd. C 1/4 S14 BT.

A hemlock, 6 ins. diam., bears S. 65 3/4° W., 12 1/2 lks. dist., mkd. C 1/4 S14 BT.

Descend over NE. slope.

42.10 Ravine, drains N. 60° E.; asc. over SE. slope.

49.95 Spur, slopes E.; desc. over broken NW. slope.

64.00 Creek, 15 lks. wide, course W.; asc. over broken NW. slope.

78.00 Creek, 5 lks. wide, course N. 80° W.; asc. over SW. slope.

79.90 The 1/4 sec. cor. of secs. 11 and 14, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1961, from original evidence no longer in existence, and further perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1965, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 12 ins. above ground, from which the remains of a bearing tree mkd. by Haines

A sawed fir stump, 30 ins. diam., bears S. 15° W., 40 lks. dist., no marks visible.

and the remains of a bearing tree mkd. by Tracy

A sawed fir stump, 11 ins. diam., bears N. 84° W., 16 1/2 lks. dist., with scribe mark B visible on opened blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.