

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 14,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon

17546

CHAINS	T 23 S    R 4 W  1/4 $\frac{S 11}{S 14}$  1982  from which new bearing trees  A fir, 5 ins. diam., bears N. 18 1/4° E., 26 lks. dist., mkd. 1/4 S11 BT.  A fir, 7 ins. diam., bears S. 64 3/4° E., 21 1/2 lks. dist., mkd. 1/4 S14 BT.
7.15	From the 1/4 sec. cor. of secs. 13 and 14.  N. 89° 47' W., on the E. and W. centerline of sec. 14.  Descend over W. slope, through heavy timber and dense undergrowth.  Creek, 10 lks. wide, course N. 40° W.; asc. over E. slope.
19.05	Spur, slopes N. 15° W.; desc. over NW. slope.
19.92	Point for the center E 1/16 sec. cor. of sec. 14.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                         C    <math>\frac{E 1/16}{S 14}</math>    C                     </div> 1982  from which  A fir, 19 ins. diam., bears N. 37° E., 11 1/2 lks. dist., mkd. CE 1/16 S14 BT.  A fir, 13 ins. diam., bears S. 9 1/4° W., 23 lks. dist., mkd. X BT.  Descend over NW. slope.
27.60	Creek, 2 lks. wide, course N. 10° E.; asc. over NE. slope.
39.60	Spur, slopes N. 10° E.; desc. over NW. slope.
39.84	The center 1/4 sec. cor. of sec. 14.  Descend over NW. slope.
43.00	Ravine, drains N. 50° E.; asc. over NE. slope.
48.00	Ridge, bears N. 30° W. and S. 30° E.; desc. over NW. slope.
66.40	Creek, 20 lks. wide, course N. 20° W.; asc. over NE. slope.
79.52	The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.