

# County Surveyor's Record, Douglas County, Oregon

17547

Subdivision of Section 14,  
T. 25 S., R. 4 W., Willamette Meridian, Oregon

| CHAINS  |  |         |      |        |       |
|---------|--|---------|------|--------|-------|
|         | <p>1/4</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 23 S</td> <td style="padding: 0 5px;">R 4 W</td> </tr> </table> <p>1976</p> <p>from which bearing trees mkd. by Jelley</p> <p style="margin-left: 40px;">A fir, 5 ins. diam., bears S. 10° E., 15 lks.<br/>dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 5 ins. diam., bears S. 21 1/4° W., 21 1/2 lks.<br/>dist., with healed blaze.</p> | S 15    | S 14 | T 23 S | R 4 W |
| S 15    | S 14   |         |      |        |       |
| T 23 S  | R 4 W  |         |      |        |       |
|         | <p>From the E 1/16 sec. cor. of secs. 14 and 23.</p> <p>N. 0° 27' E., on the N. and S. center line of the SE 1/4 of sec. 14.</p> <p>Descend over NW. slope, through heavy timber and dense undergrowth.</p>  |         |      |        |       |
| 2.05    | Creek, 4 lks. wide, course N. 50° E.; asc. over broken SE. slope.  |         |      |        |       |
| 18.70   | Spur, slopes N. 80° E.; desc. over NE. slope.  |         |      |        |       |
| 19.96   | Point for the SE 1/16 sec. cor. of sec. 14, at intersection with the E. and W. center line of the SE 1/4.  |         |      |        |       |
|         | <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">SE 1/16</td> </tr> <tr> <td style="padding: 0 5px;">S 14</td> </tr> </table> <p>1982</p>   | SE 1/16 | S 14 |        |       |
| SE 1/16 |  |         |      |        |       |
| S 14    |  |         |      |        |       |
|         | <p>from which</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears N. 54 1/2° E., 13 lks.<br/>dist., mkd. SE 1/16 S14 BT.</p> <p style="margin-left: 40px;">A fir, 4 ins. diam., bears S. 15 1/2° E., 23 1/2 lks.<br/>dist., mkd. X BT.</p> <p>Descend over NE. slope.</p>  |         |      |        |       |
| 27.40   | Spur, slopes N. 35° E.; desc. over NW. slope.  |         |      |        |       |
| 30.75   | Ravine, drains N. 40° W.; asc. over SW. slope.   |         |      |        |       |
| 35.95   | Spur, slopes N. 15° E. from S. 30° E.; desc. over NW. slope.   |         |      |        |       |
| 39.92   | The center E 1/16 sec. cor. of sec. 14.  |         |      |        |       |
|         | <p>From the S 1/16 sec. cor. of secs. 13 and 14.</p> <p>N. 89° 47' W., on the E. and W. center line of the SE 1/4 of sec. 14.</p> <p>Descend over broken NW. slope, through heavy timber and dense undergrowth.</p>  |         |      |        |       |