

County Surveyor's Record, Douglas County, Oregon

T. 31 S., R. 7 W., Willamette Meridian, Oregon **17550**

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary and subdivisional lines, and subdivision of section 32, Township 31 South, Range 7 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The south boundary and a portion of the subdivisional lines were surveyed by William H. Byars, U.S. Deputy Surveyor, in 1881-82.

A portion of the south boundary and subdivisional lines were resurveyed by Donald R. Beck, Cadastral Surveyor, in 1963-64.

A portion of the south boundary was resurveyed by Donald R. Beck, Cadastral Surveyor, in 1967.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated December 29, 1981, under Group No. 1086, Oregon.

The directions of the lines refer to the true meridian as determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming a closure were measured twice. Only those lines bounding or crossing public lands were blazed.

The geographic position of the corner of sections 4, 5, 32, and 33, on the south boundary of the township, as scaled from the quadrangle map, "DUTCHMAN BUTTE, OREGON," published by the United States Geological Survey in 1948, is as follows:

Latitude 42° 49.5' N. Longitude 123° 32.6' W.

The mean magnetic declination is 18° 30' E.

Dependent Resurvey of a Portion of the South Boundary,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by William H. Byars in 1881)

Beginning at the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

T 31 S	R 7 W
S 32	S 33
S 5	S 4
T 32 S	R 7 W

1964

from which the remains of the original bearing trees