

County Surveyor's Record, Douglas County, Oregon

17551 Dependent Resurvey, Portion of the South Boundary,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>A sawed fir stump, 34 ins. diam., bears S. 36° E., 18 lks. dist., with fragmentary scribe marks visible on bark blaze.</p> <p>A fir, 28 ins. diam., bears S. 12° W., 60 lks. dist., with fragmentary scribe marks visible on bark blaze.</p> <p>and the remains of bearing trees mkd. by Beck</p> <p>A fir, 21 ins. diam., bears N. 79 1/2° E., 88 lks. dist., with healed blaze.</p> <p>A sawed fir stump, 18 ins. diam., bears N. 54 1/4° W., 74 lks. dist., with healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 21 ins. diam., bears S. 40° E., 106 lks. dist., mkd. T32S R7W S4 BT.</p> <p>A cedar, 8 ins. diam., bears N. 58° W., 83 lks. dist., mkd. T31S R7W S32 BT.</p> <p>S. 88° 39' W., bet. secs. 5 and 32, marking and blazing the true line.</p> <p>Descend 35 ft. over NW. slope, through scattering timber and dense undergrowth.</p>
1.45	Ravine, drains N. 30° E.; asc. 120 ft. over NE. slope.
4.95	Spur, slopes N. 10° E.; asc. 50 ft. over broken NE. slope.
10.15	Spur, slopes N. 20° W.; desc. 280 ft. over NW. slope.
17.65	Ravine, drains N. 30° W.; asc. 45 ft. over NE. slope.
19.05	Spur, slopes N. 20° W.; desc. slightly over NW. slope.
19.25	Point for the E 1/16 sec. cor. of secs. 5 and 32.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S \ 32}{S \ 5}$</p> <p style="text-align: center;">1982</p> <p>from which</p> <p>A fir, 8 ins. diam., bears N. 2 1/2° E., 89 lks. dist., mkd. E 1/16 S32 BT.</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 21° W., 21 1/2 lks. dist., with brass cap mkd. RM E 1/16 S5 21 1/2 LKS 1982 and an arrow pointing to the corner.</p> <p>Descend 20 ft. over NW. slope.</p>
19.90	Ravine, drains N. 10° E.; asc. 250 ft. over broken NE. slope.