

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the South Boundary, **17552**
T. 31 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
28.95	Spur, slopes N. 20° W.; desc. 255 ft. over NW. slope.
38.50	<p>The 1/4 sec. cor. of secs. 5 and 32, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1969, monumented with the remains of the original corner tree, a sawed fir stump, 44 ins. diam., no marks visible, from which the original bearing trees</p> <p style="padding-left: 40px;">A cedar, 33 ins. diam., bears S. 82° E., 44 lks. dist., no marks visible. (Record, S. 85° E.)</p> <p style="padding-left: 40px;">A fir, 41 ins. diam., bears N. 86° W., 36 lks. dist., no marks visible. (Record, N. 80° W.)</p> <p>and bearing trees and a reference monument mkd. by Powell</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 16° E., 39 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A cedar, 18 ins. diam., bears S. 58° W., 30 lks. dist., with scribe marks 1/4 S5 CS BT visible on open double blaze.</p> <p style="padding-left: 40px;">An iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, bears West, 0.036 chs. dist., with brass cap mkd. COUNTY SURVEYORS OFFICE T31S S32 S5 R7W T32S 1969.</p> <p>Land, mountainous. Soil, rocky clay. Timber, oak, madrone, fir, cedar, pine, chinquapin, maple, and yew; undergrowth, poison oak, rhododendron, arrowwood, manzanita, ceanothus, Oregon grape, salal, fern, blackberry, huckleberry, hazel, and young timber.</p>
<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 31 S., R. 7 W., Willamette Meridian, Oregon</p>	
<p>(Restoring the survey by William H. Byars in 1882, and the resurvey by Donald R. Beck in 1963-64)</p>	
<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp.</p> <p>N. 4° 49' W., bet. secs. 32 and 33, marking and blazing the true line.</p> <p>Descend 125 ft. over NW. slope, through moderate timber and dense undergrowth.</p>	
5.40	Spur, slopes N. 20° E.; desc. 140 ft. over NW. slope.
9.20	Creek, 6 lks. wide, course N. 55° W.; asc. 205 ft. over broken SW. slope.
20.91	<p>The S 1/16 sec. cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>S 1/16</p> <p>S 32 S 33</p> <p>1964</p> </div>