

County Surveyor's Record, Douglas County, Oregon

17553 Dependent Resurvey, Portion of the Subdivisional Lines,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

from which bearing trees mkd. by Beck

A fir, 37 ins. diam., bears N. 31° E., 63 lks. dist., with healed blaze.

A fir, 16 ins. diam., bears N. 17 1/4° W., 94 lks. dist., with healed blaze.


N. 4° 47' W., beginning new measurement.

Ascend 80 ft. over SW. slope, through heavy timber and moderate undergrowth.

6.50 Spur, slopes N. 75° W.; desc. 405 ft. over broken NW. slope.

12.05 Gravelled road, 25 lks. wide, bears E. and W.

20.90 The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.



from which the remaining original bearing tree

A fir, 50 ins. diam., bears West, 37 lks. dist., with fragmentary scribe marks visible on bark blaze.

and the remains of a bearing tree mkd. by Beck

A fir snag, 15 ins. diam., bears N. 57 3/4° E., 77 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and a new bearing tree

A fir, 8 ins. diam., bears N. 19° E., 87 lks. dist., mkd. 1/4 S33 BT.

Land, mountainous.
Soil, rocky clay.
Timber, fir, cedar, yew, madrone, chinquapin, maple, oak, and alder; undergrowth, poison oak, rhododendron, manzanita, Oregon grape, salal, arrowwood, blackberry, huckleberry, and young timber.

Subdivision of Section 32,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.

N. 3° 18' W., on the N. and S. center line of sec. 32.

Ascend 100 ft. over SE. slope, through heavy timber and dense undergrowth.