

County Surveyor's Record, Douglas County, Oregon


Subdivision of Section 32,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

17554

CHAINS

- 4.55 Spur, slopes S. 40° W.; desc. 360 ft. over broken NW. slope.
- 12.50 Gravelled road, 15 lks. wide, bears N. 65° W. and E., in a curve.
- 20.95 Point for the center S 1/16 sec. cor. of sec. 32.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 17 ins. diam., bears S. 74° E., 93 lks. dist., mkd. CS 1/16 S32 BT.

A fir, 14 ins. diam., bears S. 54 1/2° W., 21 lks. dist., mkd. CS 1/16 S32 BT.

Descend 355 ft. over NW. slope.

- 30.40 Middle Creek, 25 lks. wide, course S. 70° W.; asc. 355 ft. over SE. slope.
- 31.10 Gravelled road, 25 lks. wide, bears N. 60° E. and S. 60° W.
- 41.90 Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 31 S R 7 W

C 1/4 S 32

1982

from which

A fir, 16 ins. diam., bears S. 58° E., 27 1/2 lks. dist., mkd. C 1/4 S32 BT.

A fir, 9 ins. diam., bears N. 19 1/2° W., 26 lks. dist., mkd. C 1/4 S32 BT.

Ascend 575 ft. over broken SE. slope.

- 75.30 Gravelled road, 15 lks. wide, bears N. 75° E. and S. 65° W.
- 79.05 Spur, slopes S. 40° W.; desc. 30 ft. over NW. slope, also gravelled road, 15 lks. wide, bears N. 40° E. and S. 40° W.
- 81.85 The 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.