

County Surveyor's Record, Douglas County, Oregon

17555

Subdivision of Section 32,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	$\frac{1}{4} \begin{array}{c} S 29 \\ S 32 \end{array}$ T 31 S R 7 W 1963
	from which the remains of the original bearing trees A pine stump, size indeterminate, bears S. 40° E., 11 lks. dist., no marks visible. A madrone, 24 ins. diam., bears N. 23° W., 27 lks. dist., no marks visible. and bearing trees mkd. by Beck A fir, 39 ins. diam., bears N. 30 1/2° E., 25 lks. dist., with healed blaze. A fir, 8 ins. diam., bears S. 10 1/2° W., 19 1/2 lks. dist., with healed blaze.
	From the 1/4 sec. cor. of secs. 32 and 33. S. 88° 53' W., on the E. and W. center line of sec. 32. Descend 350 ft. over NW. slope, through heavy timber and dense undergrowth.
13.75	Middle Creek, 25 lks. wide, course S. 30° W.; asc. 175 ft. over SE. slope.
14.45	Gravelled road, 25 lks. wide, bears N. 30° E. and S. 30° W.
18.71	Point for the center E 1/16 sec. cor. of sec. 32. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	$C \frac{E 1/16}{S 32} C$ 1982
	from which A fir, 12 ins. diam., bears S. 30 1/2° E., 87 lks. dist., mkd. CE 1/16 S32 BT. A fir, 23 ins. diam., bears N. 5° W., 53 lks. dist., mkd. CE 1/16 S32 BT.
	Ascend 210 ft. over SE. slope.
37.42	The center 1/4 sec. cor. of sec. 32. Ascend 130 ft. over SE. slope.
53.40	Spur, slopes S. 10° W.; desc. 405 ft. over SW. slope.
64.85	Creek, 6 lks. wide, course S. 40° E.; asc. 350 ft. over NE. slope.
79.63	The 1/4 sec. cor. of secs. 31 and 32, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, and further perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1972, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.