

County Surveyor's Record, Douglas County, Oregon

17556

Subdivision of Section 32,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 31 S R 7 W
1/4 S 31 | S 32
1963

from which the remaining original bearing tree

A fir, 30 ins. diam., bears N. 36° E., 20 lks.
dist., with scribe marks 1/4 S32 CS BT visible
on opened blaze. (Record, 17 lks.)

and a bearing tree mkd. by Powell

A fir, 14 ins. diam., bears S. 70° W., 353 lks.
dist., with healed double blaze.

and a new bearing tree

A fir, 5 ins. diam., bears S. 83 1/4° W., 72 lks.
dist., mkd. X BT.

From the E 1/16 sec. cor. of secs. 5 and 32, on the
S. bdy. of the Tp.

N. 4° 03' W., on the N. and S. center line of the SE 1/4 of
sec. 32.

Descend 85 ft. over broken NW. slope, through scattering
timber and dense undergrowth.

2.90 Gravelled road, 20 lks. wide, bears N. 20° E. and
N. 60° W., in a curve, also ravine, drains N. 10° E.;
desc. 175 ft. over broken NE. slope.

20.93 Point for the SE 1/16 sec. cor. of sec. 32, at intersec-
tion with the E. and W. center line of the SE 1/4.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in
the ground, with brass cap mkd.

SE 1/16 S 32
1982

from which

A fir, 26 ins. diam., bears N. 34 1/2° E., 77 lks.
dist., mkd. SE 1/16 S32 BT.

A fir, 18 ins. diam., bears N. 58° W., 68 lks.
dist., mkd. SE 1/16 S32 BT.

Descend 350 ft. over NE. slope.

35.55 Middle Creek, 40 lks. wide, course S. 80° W.; asc.
150 ft. over SE. slope.

37.00 Gravelled road, 25 lks. wide, bears N. 55° E. and W., in
a curve.

41.86 The center E 1/16 sec. cor. of sec. 32.