

County Surveyor's Record, Douglas County, Oregon

17559

T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and subdivision of section 2, Township 32 South, Range 7 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The north boundary and subdivisional lines were surveyed by William H. Byars, U.S. Deputy Surveyor, in 1881.

A portion of the north boundary and subdivisional lines were resurveyed by Donald R. Beck, Cadastral Surveyor, in 1963-64.

A portion of the subdivisional lines was resurveyed by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, in 1978.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated December 29, 1981, under Group No. 1086, Oregon.

The directions of the lines refer to the true meridian as determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming a closure were measured twice. Only those lines bounding or crossing public lands were blazed.

The geographic positions of the corner of sections 1, 2, 11, and 12, as scaled from the quadrangle map, "CANYONVILLE, OREGON," published by the United States Geological Survey in 1954, is as follows:

Latitude 42° 48.7' N. Longitude 123° 29.1' W.

The mean magnetic declination is 18° 30' E.

Dependent Resurvey of
a Portion of the Subdivisional Lines,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by William H. Byars in 1881,
and the resurvey by Donald R. Beck in 1964)

Beginning at the 1/4 sec. cor. of secs. 1 and 2, perpetuated and recorded by Howard W. Johnstone, Registered Land Surveyor, No. 498, in 1969, monumented with an iron pipe, 1 in. diam., firmly set, projecting 2 ins. above ground, from which the original bearing trees

A madrone, 18 ins. diam., bears S. 32° E.,
12 lks. dist., with scribe marks 1/4 visible on
opened blaze.