

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, **17560**
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS


A fir, 32 ins. diam., bears S 11° E., 22 lks. dist., with scribe marks 1/4 S B visible on bark blaze. (Record, S. 5° W.)

and a bearing tree mkd. by Johnstone

A fir, 20 ins. diam., bears S. 63° E., 73 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



from which a new bearing tree

A fir, 13 ins. diam., bears S. 83 1/2° W., 216 lks. dist., mkd. 1/4 S2 BT.

Reset iron pipe alongside iron post.


N. 0° 22' W., bet. secs. 1 and 2, marking and blazing the true line.

Descend 35 ft. over NE. slope, through heavy timber and dense undergrowth.

1.70 Ravine, drains N. 80° E.; asc. 45 ft. over SE. slope.

4.25 Spur, slopes E.; desc. 270 ft. over broken NE. slope.

20.95 The N 1/16 sec. cor. of secs. 1 and 2, established and recorded by Howard W. Johnstone, Registered Land Surveyor, No. 498, in 1969, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, with 1 in. diam., aluminum cap mkd.



from which bearing trees mkd. by Johnstone

A fir, 6 ins. diam., bears S. 20° E., 55 1/2 lks. dist., with healed double blaze.

A fir, 8 ins. diam., bears N. 4 1/2° W., 78 lks. dist., with healed double blaze.

N. 0° 22' W., beginning new measurement.

Descend 280 ft. over NE. slope.

10.90 Martin Creek, 20 lks. wide, course N. 55° W.; asc. 80 ft. over SW. slope.