

County Surveyor's Record, Douglas County, Oregon

17561

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

20.45

Gravelled road, 25 lks. wide, bears N. 75° W. and S. 75° E.

24.10

The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

T 31 S R 7 W

S 35	S 36
------	------

S 2	S 1
-----	-----

T 32 S R 7 W

1964

from which the remains of the original bearing trees

A sawed fir stump, 37 ins. diam., bears N. 80° E., 50 lks. dist., no marks visible.

A root hole, bears S. 20° E., 12 lks. dist., with a down fir alongside, 18 ins. diam., with healed blaze.

A fir, 16 ins. diam., bears S. 60° W., 15 lks. dist., with healed blaze.

and a bearing tree mkd. by Howard W. Johnstone, Registered Land Surveyor, No. 498, in 1969

A fir, 15 ins. diam., bears N. 9° W., 32 lks. dist., with healed blaze.

and a new bearing tree

A fir, 15 ins. diam., bears S. 17° E., 122 lks. dist., mkd. T32S R7W S1 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, pine, willow, alder, maple, yew, oak, madrone, and chinquapin; undergrowth, Oregon grape, poison oak, salal, hazel, arrowwood, ferns, manzanita, huckleberry, and young timber.

From the cor. of secs. 1, 2, 11, and 12, perpetuated by Howard W. Johnstone, Registered Land Surveyor, No. 498, in 1961 and recorded in 1969, and further perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966-67, monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, from which the remains of the original bearing trees

A fir, 36 ins. diam., bears N. 5° E., 12 lks. dist., with scribe marks T32S R7W S1 BT visible on bark blaze.

A sawed fir stump, 48 ins. diam., bears S. 50° E., 61 lks. dist., with scribe marks R7W visible on bark blaze.

A fir, 34 ins. diam., bears S. 20° W., 96 lks. dist., with scribe marks T32S R7W S11 visible on bark blaze. (Record, 100 lks.)

A sawed fir stump, 40 ins. diam., bears N. 40° W., 9 lks. dist., no marks visible.