

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, **17562**
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

and the remains of bearing trees mkd. by Powell

A fir, 10 ins. diam., bears N. 48 1/2° E., 16 lks. dist., with healed double blaze.

A fir, 7 ins. diam., bears S. 15° E., 41 lks. dist., with healed double blaze.

A root hole, bears S. 35° W., 46 lks. dist., with a down madrone alongside, 8 ins. diam., with scribe marks 32S R7W S11 CS visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 7 W

S 2	S 1
S 11	S 12

1982

from which a new bearing tree

A fir, 7 ins. diam., bears N. 55° W., 47 lks. dist., mkd. T32S R7W S2 BT.

Reset iron pipe alongside iron post.

N. 89° 59' W., bet. secs. 2 and 11.

Descend 350 ft. over NW. slope, through heavy timber and dense undergrowth.

14.10 Creek, 5 lks. wide, course N. 55° W.; asc. 250 ft. over broken NE. slope.

35.60 Spur, slopes N. 35° W.; desc. 75 ft. over SW. slope.

39.49 Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 32 S R 7 W

1/4	S 2	S 11
-----	-----	------

1982

from which

A fir, 8 ins. diam., bears N. 32 1/2° E., 22 lks. dist., mkd. 1/4 S2 BT.

A fir, 8 ins. diam., bears S. 80 1/2° W., 39 1/2 lks. dist., mkd. 1/4 S11 BT.

Descend 315 ft. over SW. slope.

53.80 Creek, 5 lks. wide, course NW.; asc. 255 ft. over NE. slope.