

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, **17566**
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

19.49

The S 1/16 sec. cor. of secs. 5 and 6, established and recorded by Howard W. Johnstone, Registered Land Surveyor, No. 498, in 1980, and is accepted as the corner, monumented with an iron rod, 3/8 in. diam., firmly set, projecting 8 ins. above ground, with an aluminum cap, 2 ins. diam., mkd.

T 32 S R 7 W
S 1/16
6 | 5
1980
LS 498

from which bearing trees mkd. by Johnstone

A fir, 9 ins. diam., bears S. 28° E., 28 1/2 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A fir, 15 ins. diam., bears N. 22° W., 26 1/2 lks. dist., with scribe marks BT visible on partially healed blaze.

N. 2° 17' W., beginning new measurement.

Ascend 65 ft. over SE. slope.

3.25

Ridge, bears N. 75° E. and S. 75° W.; desc. 505 ft. over broken NE. slope; also dirt road, 20 lks. wide, bears N. 75° E. and S. 75° W.

19.56

The 1/4 sec. cor. of secs. 5 and 6, reestablished by proportionate measurement and recorded by Howard W. Johnstone, Registered Land Surveyor, No. 498, in 1980, and is accepted as the best available evidence of the position of the original corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, with an aluminum cap, 2 ins. diam., mkd.

T 32 S R 7 W
1/4
6 | 5
1980
LS 498

from which bearing trees mkd. by Johnstone

A fir, 5 ins. diam., bears S. 62° E., 6 1/2 lks. dist., with scribe marks 1/4 S5 BT visible on open blaze.

A tan oak, 5 ins. diam., bears S. 67° W., 13 1/2 lks. dist., with scribe marks 1/4 S6 BT visible on open blaze.

N. 2° 22' W., beginning new measurement.

Descend 195 ft. over NE. slope.

4.60

Creek, 3 lks. wide, course N. 20° E.; asc. 40 ft. over broken SE. slope.