

County Surveyor's Record, Douglas County, Oregon

17567 Dependent Resurvey, Portion of the Subdivisional Lines,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS													
19.49	<p>The N 1/16 sec. cor. of secs. 5 and 6, established and recorded by Howard W. Johnstone, Registered Land Surveyor, No. 498, in 1980, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with aluminum cap, 2 ins. diam., mkd.</p> <div style="text-align: center;"> <p>T 32 S R 7 W N 1/16</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 5px 0;">1980 LS 498</td> </tr> </table> </div> <p>from which bearing trees mkd. by Johnstone</p> <p style="margin-left: 40px;">A fir, 41 ins. diam., bears N. 55° E., 51 lks. dist., with scribe marks N 1/16 visible on partially healed blaze.</p> <p style="margin-left: 40px;">A madrone, 11 ins. diam., bears N. 27° W., 25 lks. dist., with scribe marks 1/16 S6 BT visible on open blaze.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 2° 24' W., beginning new measurement.</p> <p>Ascend 5 ft. over SE. slope.</p>	S 6	S 5	1980 LS 498									
S 6	S 5												
1980 LS 498													
0.40	<p>Spur, slopes N. 40° E.; desc. 540 ft. over NE. slope.</p>												
9.95	<p>Gravelled road, 25 lks. wide, bears N. 65° W. and S. 70° E.</p>												
15.25	<p>Creek, 4 lks. wide, course N. 40° W.; asc. 70 ft. over SW. slope.</p>												
19.96	<p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>COUNTY SURVEYORS OFFICE T 31 S</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 31</td> <td style="padding: 0 5px;">S 32</td> <td style="padding: 0 5px;">R</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black; text-align: center; padding: 2px 0;">7</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">W</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 5px 0;">T 32 S 1980</td> <td></td> </tr> </table> </div> <p>from which the remaining original bearing trees</p> <p style="margin-left: 40px;">A fir, 25 ins. diam., bears N. 10° E., 58 lks. dist., with scribe marks 3S RS visible on bark blaze.</p> <p style="margin-left: 40px;">A fir, 45 ins. diam., bears S. 32° W., 38 lks. dist., no marks visible.</p> <p>and bearing trees mkd. by Byron</p> <p style="margin-left: 40px;">A madrone, 14 ins. diam., bears S. 19° E., 44 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.</p>	S 31	S 32	R	7			S 6	S 5	W	T 32 S 1980		
S 31	S 32	R											
7													
S 6	S 5	W											
T 32 S 1980													