

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, **17568**  
 T. 32 S., R. 7 W., Willamette Meridian, Oregon

| CHAINS |  |
|--------|--|
|        | <p>A canyon live oak, 7 ins. diam., bears S. 76° W., 43 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.</p> <p>A madrone, 9 ins. diam., bears N. 37 3/4° W., 28 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.</p> <p>Land, mountainous.<br/>                     Soil, rocky clay.<br/>                     Timber, oak, maple, fir, yew, pine, cedar, alder, madrone, chinquapin, and ash; undergrowth, vine maple, poison oak, manzanita, ceanothus, huckleberry, arrowwood, hazel, blackberry, rhododendron, fern, salal, Oregon grape, and young timber.</p> |
|        | <p>Subdivision of Section 2,<br/>                     T. 32 S., R. 7 W., Willamette Meridian, Oregon</p>   |
|        | <p>From the 1/4 sec. cor. of secs. 2 and 11.</p> <p>N. 1° 04' W., on the N. and S. center line of sec. 2.</p> <p>Ascend 20 ft. over broken SW. slope, through moderate timber and dense undergrowth.</p>   |
| 5.15   | Spur, slopes N. 50° W.; desc. 355 ft. over NE. slope.  |
| 16.35  | Buck Creek, 8 lks. wide, course NW.; asc. 85 ft. over SW. slope.   |
| 17.50  | Gravelled road, 20 lks. wide, bears N. 40° W. and S. 40° E.  |
| 27.70  | Spur, slopes W.; desc. 80 ft. over NW. slope.  |
| 29.15  | Ravine, drains W.; asc. 5 ft. over SW. slope.  |
| 40.20  | Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E. and W. center line.  |
|        | <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 S    R 7 W<br/>                     C 1/4<br/>                     S 2<br/>                     1982</p>   |
|        | <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 1° E., 101 lks. dist., mkd. C 1/4 S2 BT.</p> <p style="padding-left: 40px;">A yew, 10 ins. diam., bears S. 23° W., 117 lks. dist., mkd. C 1/4 S2 BT.</p> <p>Ascend 185 ft. over SW. slope.</p>  |
| 60.20  | Spur, slopes SW.; desc. 10 ft. over NW. slope.   |
| 60.905 | Point for the center N 1/16 sec cor. of sec. 2.  |
|        | <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>  |