

# County Surveyor's Record, Douglas County, Oregon

17569

Subdivision of Section 2,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	$  \begin{array}{c}  C \\    \\  N \ 1/16 \quad   \quad S \ 2 \\    \\  C \\  \\  1982  \end{array}  $
	<p>from which</p> <p style="margin-left: 40px;">A fir, 7 ins. diam., bears S. 54 1/2° E., 29 lks. dist., mkd. CN 1/16 S2 BT.</p> <p style="margin-left: 40px;">A fir, 5 ins. diam., bears S. 75° W., 11 lks. dist., mkd. X BT.</p> <p>Descend 120 ft. over NW. slope.</p>
67.30	Ravine, drains S. 70° W.; asc. 270 ft. over broken S. slope.
79.85	Spur, slopes S. 55° W.; desc. 25 ft. over NW. slope.
84.32	The 1/4 sec. cor. of secs. 2 and 35, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	$  \begin{array}{c}  T \ 31 \ S \quad R \ 7 \ W \\  1/4 \ \frac{S \ 35}{S \ 2} \\  T \ 32 \ S \quad R \ 7 \ W \\  \\  1964  \end{array}  $
	<p>from which the remaining original bearing tree</p> <p style="margin-left: 40px;">A fir, 48 ins. diam., bears N. 10° W., 48 lks. dist., no marks visible.</p> <p>and bearing trees mkd. by Beck</p> <p style="margin-left: 40px;">A fir, 21 ins. diam., bears N. 44 1/2° E., 38 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears S. 5° W., 65 lks. dist., with healed blaze. (Record, 68 lks.)</p>
	<p>From the 1/4 sec. cor. of secs. 1 and 2.</p> <p>N. 89° 22' W., on the E. and W. center line of sec. 2.</p> <p>Ascend 335 ft. over broken NE. slope, through moderate timber and dense undergrowth.</p>
9.55	Ridge, bears N. 15° W. and S.; desc. 335 ft. over broken NW. slope, changing to SW. slope.
9.95	Gravelled road, 15 lks. wide, bears N. and S.
19.85	Point for the center E 1/16 sec. cor. of sec. 2.
	<p>Set an aluminum post, 23 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>